HEAVY DUTY STOVE 4 BURNERS | INCLUDING ELECTRIC OVEN









GENERAL SPECIFICATIONS

- 1.5 mm thick AISI 304 stainless steel top
- Flush top setting with secure fixing screws
- Installation gap behind the equipment
- Easy access from front panel to all major components
- Stainless steel with satin Scotch-Brite finish
- Adjustable feet


INSTALLATION OPTIONS

- standalone (fixed on a base w/ or w/o door)
- cantilever
- on concrete plinth

GAS FLOW RATE

68240 Btu/hr **17200** kcal

G20 Natural gas 20mbar 2.11 m³/h G30/G31 LPG 28-30/37 mbar 1.57 kg/h G30 LPG 50 mbar 1.57 kg/h















OPEN BURNERS

- Each open burner equipped with flame failure device to make usage comfortable and safe
- Each open burner has a pan support made from cast iron
- Burners with optimized combustion

ELECTRIC OVEN

- AISI 430 S/S, 2/1 GN capacity static oven chamber
- 4 position switch: Off, Top, Bottom or both
- 40 mm thick oven door equipped with ergonomic handle
- Thermostatically controlled oven temperature between 50-300°C
- Spring counterbalanced heavy duty door Gasket-free designed oven door

OPTIONS

Electric Ignition

ACCESSORIES

- GN 2/1 chrome grid for static oven 1 Pcs
- Flame reducer 1 Pcs

